



GROWING TOGETHER

ROW CROP

AGRICULTURAL TIRES








AGRICULTURAL TIRES

ROW CROP

If you are looking for a tire that is suitable for row crops, BKT has the right answer for your needs. Specifically designed for the different types of land for vineyard and orchard crops, BKT offers an extensive range of highly performing tires. Available in a large number of sizes appropriate for the different types of machinery, these tires are your best ally for row crops.

Distinguishing marks? High load capacity and improved traction as well as reduced soil compaction. BKT tires offer the perfect mix of performance, efficiency, durability and riding comfort.

TECHNOLOGIES AND PERFORMANCE



Radials

Radial tires have cord plies that are arranged running radially from bead to bead around the tire. Sidewall and tread have independent functional features providing more flexibility, great performance, durability, and fuel economy.



Bias

Bias tires have cord plies that are arranged running diagonally from bead to bead across the tire. Layers overlap forming a crisscross pattern. This design features extraordinary sidewall resistance, puncture resistance and high load capacity.

ROW CROP TIRES



AGRIMAX RT 855



[p. 6]



AGRIMAX SPARGO



[p. 12]



AGRIMAX RT 945



[p. 14]



AGRIMAX RT 955



[p. 16]





Radial

R-1W

D

176

Performance



Traction



Self-Cleaning



High Load Capacity



Handling & Comfort



AGRIMAX RT 855

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Ø 16"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	180/95 R 16	105 A8/B	5.5 F	6.0 F	185	760	340	2265	360	STD
	210/95 R 16	106 A8/B	W 7	W 6; 6 LB	214	806	360	2415	390	STD
Ø 18"	210/95 R 18	108 A8/B	W 7	W 6	214	855	385	2557	410	STD
Ø 20"	210/90 R 20	110 A8/B	W 7	W 6	211	890	412	2681	425	STD
	210/95 R 20	110 A8/B	W 7	W 6	214	908	418	2749	450	STD
	250/85 R 20	116 A8/B	W 8	W 7; W 9	250	940	424	2812	450	STD
	280/85 R 20	112 A8/B	W 10	W 9	292	984	441	2952	475	STD
	320/85 R 20	119 A8/B	W 11	W 9; W 10	329	1052	467	3100	500	STD
Ø 22"	250/85 R 22	113 A8/B	W 8	W 7	251	985	453	2964	475	STD
	250/85 R 22	113 A8/B	W 8	W 7	251	985	453	2964	475	SPL
Ø 24"	250/85 R 24	109 A8/B	W 8	W 7; W 9	251	1036	475	3104	500	STD
	250/85 R 24	109 A8/B	W 8	W 7; W 9	251	1036	475	3104	500	SPL
	280/85 R 24	115 A8/B	W 10	W 9	292	1086	492	3224	525	STD
	280/85 R 24	115 A8/B	W 10	W 9	292	1086	492	3224	525	SPL
	320/85 R 24	122 A8/B	W 11	W 9; W 10	329	1154	519	3413	550	STD

STD: Standard - SPL: Special



Ø 24"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	320/85 R 24	122 A8/B	W 11	W 9; W 10	329	1154	519	3413	550	SPL
	340/85 R 24	125 A8/B	W 12	W 11	353	1188	531	3540	575	STD
	340/85 R 24	125 A8/B	W 12	W 11	353	1188	531	3540	575	SPL
	380/85 R 24	131 A8/B	W 12	W 11; W 13	380	1256	554	3699	600	STD
	380/85 R 24	131 A8/B	W 12	W 11; W 13	380	1256	554	3699	600	SPL
	420/85 R 24	137 A8/B	W 15 L	W 14 L; W 13	438	1324	582	3900	625	STD
	420/85 R 24	137 A8/B	W 15 L	W 14 L; W 13	438	1324	582	3900	625	SPL
Ø 28"	250/85 R 28	112 A8/B	W 8	W 7; W 9	251	1137	519	3421	550	STD
	250/85 R 28	112 A8/B	W 8	W 7; W 9	251	1137	519	3421	550	SPL
	280/85 R 28	118 A8/B	W 10	W 9	292	1187	545	3558	575	STD
	280/85 R 28	118 A8/B	W 10	W 9	292	1187	545	3558	575	SPL
	320/85 R 28	124 A8/B	W 11	W 9; W 10	329	1255	569	3743	600	STD
	320/85 R 28	124 A8/B	W 11	W 9; W 10	329	1255	569	3743	600	SPL
	340/85 R 28	127 A8/B	W 12	W 11	353	1289	588	3890	625	STD
	340/85 R 28	127 A8/B	W 12	W 11	353	1289	588	3890	625	SPL

STD: Standard - SPL: Special





Radial

R-1W

D

176

Performance



Self-Cleaning



High Load Capacity



Handling & Comfort



AGRIMAX RT 855

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.



Ø 28"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	380/85 R 28	133 A8/B	W 12	W 11; W 13	380	1357	606	4015	650	STD
	380/85 R 28	133 A8/B	W 12	W 11; W 13	380	1357	606	4015	650	SPL
	420/85 R 28	139 A8/B	W 15 L	W 13; W 14 L	438	1425	638	4214	675	STD
	420/85 R 28	139 A8/B	W 15 L	W 13; W 14 L	438	1425	638	4214	675	SPL
Ø 30"	380/85 R 30	135 A8/B	W 12	W 11; W 13	380	1408	633	4169	675	STD
	380/85 R 30	135 A8/B	W 12	W 11; W 13	380	1408	633	4169	675	SPL
	420/85 R 30	140 A8/B	W 15 L	W 13; W 14 L	438	1475	661	4393	700	STD
	420/85 R 30	140 A8/B	W 15 L	W 13; W 14 L	438	1475	661	4393	700	SPL
	460/85 R 30	145 A8/B	W 16 L	W 14 L; W 15 L	475	1544	680	4529	725	STD
	460/85 R 30	145 A8/B	W 16 L	W 14 L; W 15 L	475	1544	680	4529	725	SPL
	460/85 R 30	156 A8/B	W 16 L	W 14 L; W 15 L	475	1544	680	4529	725	STD
Ø 32"	320/85 R 32	126 A8/B	W 11	W 9; W 10	329	1357	621	4081	650	STD
	320/85 R 32	126 A8/B	W 11	W 9; W 10	329	1357	621	4081	650	SPL
Ø 34"	320/85 R 34	141 A8/B	W 11	W 9; W 10	329	1408	645	4280	675	STD
	320/85 R 34	141 A8/B	W 11	W 9; W 10	329	1408	645	4280	675	SPL

STD: Standard - SPL: Special

Ø 34"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	380/85 R 34	137 A8/B	W 12	W 11; W 13	380	1509	682	4504	725	STD
	380/85 R 34	137 A8/B	W 12	W 11; W 13	380	1509	682	4504	725	SPL
	420/85 R 34	142 A8/B	W 15 L	W 13; W 14 L	438	1578	709	4677	750	STD
	420/85 R 34	142 A8/B	W 15 L	W 13; W 14 L	438	1578	709	4677	750	SPL
	420/85 R 34	147 A8/B	W 15 L	W 13; W 14 L	438	1578	709	4677	750	STD
	460/85 R 34	147 A8/B	W 16 L	W 14 L; W 15 L	475	1646	721	4865	775	STD
	460/85 R 34	147 A8/B	W 16 L	W 14 L; W 15 L	475	1646	721	4865	775	SPL
	460/85 R 34	158 A8/B	W 16 L	W 14 L; W 15 L	475	1646	721	4865	775	STD
Ø 36"	320/85 R 36	128 A8/B	W 11	W 9; W 10	329	1458	672	4404	700	STD
	320/85 R 36	128 A8/B	W 11	W 9; W 10	329	1458	672	4404	700	SPL
	320/85 R 36	147 D/150 A8	W 11	W 9; W 10	329	1458	672	4404	700	STD
	340/85 R 36	132 A8/B	W 12	W 11	353	1492	689	4507	725	STD
	340/85 R 36	132 A8/B	W 12	W 11	353	1492	689	4507	725	SPL
Ø 38"	320/85 R 38	143 A8/B	W 10	W 9; W 11; DW 11	319	1509	700	4580	725	STD
	320/85 R 38	143 A8/B	W 10	W 9; W 11; DW 11	319	1509	700	4580	725	SPL

STD: Standard - SPL: Special



Radial

R-1W

D

176

Performance



Traction



Self-Cleaning



High Load Capacity



Handling & Comfort



AGRIMAX RT 855

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Ø 38"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	340/85 R 38	133 A8/B	W 12	W 11	353	1543	712	4613	750	STD
	340/85 R 38	133 A8/B	W 12	W 11	353	1543	712	4613	750	SPL
	380/85 R 38	139 A8/B	W 12	W 11 ; W 13	380	1611	736	4841	775	STD
	380/85 R 38	139 A8/B	W 12	W 11 ; W 13	380	1611	736	4841	775	SPL
	420/85 R 38	144 A8/B	W 15 L	W 13 ; W 14 L	438	1679	763	4992	800	STD
	420/85 R 38	144 A8/B	W 15 L	W 13 ; W 14 L	438	1679	763	4992	800	SPL
	460/85 R 38	149 A8/B	W 16 L	W 14 L ; W 15 L	475	1747	785	5161	825	STD
	460/85 R 38	149 A8/B	W 16 L	W 14 L ; W 15 L	475	1747	785	5161	825	SPL
	480/80 R 38	149 A8/B	W 16 L	W 14 L ; W 15 L	475	1747	785	5161	825	STD
	520/85 R 38	155 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5393	875	STD
	520/85 R 38	155 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5393	875	SPL
	520/85 R 38	170 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5393	875	STD
	520/85 R 38	170 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5393	875	SPL
Ø 42"	480/80 R 42	151 A8/B	W 16 A ; DD 16 ; DW 16 A	DD 16 L ; DW 16 L ; W 16 L	479	1835	835	5459	875	STD
	520/85 R 42	157 A8/B	DW 16 A ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5735	925	STD

STD: Standard - SPL: Special



Ø 42"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	520/85 R 42	157 A8/B	DW 16 A ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5735	925	SPL
	520/85 R 42	167 A8/B	DW 16 A ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5735	925	STD
	520/85 R 42	167 A8/B	DW 16 A ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5735	925	SPL
Ø 46"	420/80 R 46	151 D/162 A2	W 13	W 12	418	1840	863	5619	875	STD
	420/80 R 46	159 D/170 A2	W 13	W 12	418	1840	863	5619	875	STD
	420/80 R 46	159 D/170 A2	W 13	W 12	418	1840	863	5619	875	SPL
	480/80 R 46	158 A8/B	DW 16 A ; W 16 A ; DD 16	W 16 L ; DD 16 L ; DW 16 L	479	1936	895	5871	925	STD
	480/80 R 46	164 A8/B	DW 16 A ; W 16 A ; DD 16	W 16 L ; DD 16 L ; DW 16 L	479	1936	895	5871	925	STD
	520/85 R 46	158 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2052	949	6252	975	STD
	520/85 R 46	158 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2052	949	6252	975	SPL
	520/85 R 46	173 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2052	949	6252	975	STD
Ø 50"	480/80 R 50	159 A8/B	DW 16 A	DW 15 A ; W 15 A	489	2036	941	6158	975	STD
	480/80 R 50	176 A8	DW 16 A	DW 15 A ; W 15 A	489	2036	945	6228	975	SB
	520/85 R 50	165 A8/B	DW 16 L	DW 18 L	516	2154	992	6472	1025	STD

STD: Standard - SPL: Special - SB: Steel Belted



Radial



Technology



VF Technology



Strong Casing



More Lugs

Performance



High Load Capacity



Durability



Stability



AGRIMAX SPARGO

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

Ø 38"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	VF 380/85 R 38	161 D	W 13	W 12	380	1602	730	4830	775	STD
Ø 46"	VF 380/90 R 46	173 D	DW 13 A	W 13 A ; DW 12	390	1852	846	5611	925	STD
	VF 480/80 R 46	177 D	DW 16 L	DW 15 L	479	1936	889	5861	925	STD

STD: Standard



Ø 50"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	VF 380/105 R 50	179 D	DW 13	TW 13 ; W 13	400	2050	934	6211	1025	STD
	VF 420/95 R 50	177 D	DW 14	DW 13 ; W 13 ; W 14	419	2068	943	6210	1025	STD
	VF 480/80 R 50	179 D	DW 16 L	DW 15 L	479	2038	940	6172	975	STD

STD: Standard





Radial

R-1W

D

159

Technology



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction



AGRIMAX RT 945

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

Ø 30"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	420/90 R 30	147 A8/B	DW13	-	418	1518	684	4571	725	STD
Ø 42"	320/90 R 42	139 A8/B	W 10	W 9; W 11	319	1643	760	4944	800	STD
	320/90 R 42	139 A8/B	W 10	W 9; W 11	319	1643	760	4944	800	SPL
Ø 46"	320/90 R 46	146 A8/B	W 10	W 9; W 11	319	1744	810	5232	825	STD
	320/90 R 46	146 A8/B	W 10	W 9; W 11	319	1744	810	5232	825	SPL
	320/90 R 46	148 D/151 A8	W 10	W 9; W 11	319	1744	810	5232	825	STD
	320/90 R 46	148 D/151 A8	W 10	W 9; W 11	319	1744	810	5232	825	SPL
	380/90 R 46	155 A8/B	W 12	W 11; W 13	380	1852	859	5596	875	STD
	380/90 R 46	159 A8/B	W 12	W 11; W 13	380	1852	859	5596	875	STD

STD: Standard - SPL: Special



Ø 46"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	380/90 R 46	159 A8/B	W 12	W 11; W 13	380	1852	859	5596	875	SPL
Ø 50"	320/90 R 50	150 A8/B	W 10	W 9; W 11	319	1846	873	5618	875	STD
	320/90 R 50	150 A8/B	W 10	W 9; W 11	319	1846	873	5618	875	SPL
	380/90 R 50	151 A8/B	W 12	W 11; W 13	380	1954	913	5902	975	STD
	380/90 R 50	151 A8/B	W 12	W 11; W 13	380	1954	913	5902	975	SPL
Ø 54"	320/90 R 54	156 A8/B	W 10	W 9; W 11	319	1948	930	5987	925	STD
	320/90 R 54	156 A8/B	W 10	W 9; W 11	319	1948	930	5987	925	SPL
	380/90 R 54	158 A8/B	W 12	W 11; W 13	380	2056	962	6296	1025	STD
	380/90 R 54	158 A8/B	W 12	W 11; W 13	380	2056	962	6296	1025	SPL

STD: Standard - SPL: Special





Radial



Technology



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction



AGRIMAX RT 955

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

Ø 24"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	210/90 R 24	107 A8/B	W 7	W 6	214	1010	462	3027	475	STD
	210/90 R 24	107 A8/B	W 7	W 6	214	1010	462	3027	475	SPL
Ø 28"	210/95 R 28	116 A8/B	W 7	W 6	214	1111	513	3364	550	STD
	210/95 R 28	116 A8/B	W 7	W 6	214	1111	513	3364	550	SPL
Ø 32"	210/95 R 32	120 A8/B	W 7	W 6	214	1213	571	3703	575	STD
	210/95 R 32	120 A8/B	W 7	W 6	214	1213	571	3703	575	SPL
	230/95 R 32	128 A8/B	W 8	W 7	238	1251	585	3792	600	STD
	230/95 R 32	128 A8/B	W 8	W 7	238	1251	585	3792	600	SPL
	270/95 R 32	136 A8/B	W 9	W 8 ; W 10	275	1327	614	4044	625	STD
	270/95 R 32	136 A8/B	W 9	W 8 ; W 10	275	1327	614	4044	625	SPL
Ø 36"	230/95 R 36	130 A8/B	W 8	W 7	238	1352	639	4112	650	STD
	230/95 R 36	130 A8/B	W 8	W 7	238	1352	639	4112	650	SPL
	270/95 R 36	139 A8/B	W 9	W 8 ; W 10	275	1428	665	4368	675	STD
	270/95 R 36	139 A8/B	W 9	W 8 ; W 10	275	1428	665	4368	675	SPL
Ø 38"	270/95 R 38	140 A8/B	W 9	W 8 ; W 10	275	1479	697	4510	700	STD

STD: Standard - SPL: Special



Ø 38"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	270/95 R 38	140 A8/B	W 9	W 8 ; W 10	275	1479	697	4510	700	SPL
Ø 40"	230/95 R 40	132 A8/B	W 7	W 8	228	1454	690	4445	700	STD
	230/95 R 42	133 A8/B	W 8	W 7	238	1506	714	4633	725	STD
Ø 42"	230/95 R 42	133 A8/B	W 8	W 7	238	1506	714	4633	725	SPL
	300/85 R 42	144 A8/B	W 9	W 10 ; W 11	295	1577	745	4850	750	STD
	300/85 R 42	144 A8/B	W 9	W 10 ; W 11	295	1577	745	4850	750	SPL
Ø 44"	210/95 R 44	120 A8/B	W 7	W 6	214	1518	721	4653	725	STD
	210/95 R 44	120 A8/B	W 7	W 6	214	1518	721	4653	725	SPL
	230/95 R 44	134 A8/B	W 8	W 7	238	1556	739	4788	750	STD
	230/95 R 44	134 A8/B	W 8	W 7	238	1556	739	4788	750	SPL
	270/95 R 44	142 A8/B	W 9	W 8 ; W 10	275	1632	764	4983	775	STD
	270/95 R 44	142 A8/B	W 9	W 8 ; W 10	275	1632	764	4983	775	SPL
Ø 46"	270/95 R 46	143 A8/B	W 9	W 8 ; W 10	275	1683	786	5049	825	STD
	270/95 R 46	143 A8/B	W 9	W 8 ; W 10	275	1683	786	5049	825	SPL
	300/95 R 46	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	STD

STD: Standard - SPL: Special



Radial



Technology



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction



AGRIMAX RT 955

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.



Ø 46"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	300/95 R 46	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	SPL
	340/85 R 46	150 A8/B	W 12	W 11	353	1746	811	5238	825	STD
Ø 48"	Tire size	LI/SS	Rec.	Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
	230/95 R 48	136 A8/B	W 8	W 7	238	1656	792	5085	800	STD
	230/95 R 48	136 A8/B	W 8	W 7	238	1656	792	5085	800	SPL
	270/95 R 48	144 A8/B	W 9	W 8 ; W 10	275	1733	820	5351	825	STD
	270/95 R 48	144 A8/B	W 9	W 8 ; W 10	275	1733	820	5351	825	SPL

STD: Standard - SPL: Special

Ø 48"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	340/85 R 48	152 A8/B	W 12	W 11	353	1797	855	5572	875	STD
	340/85 R 48	152 A8/B	W 12	W 11	353	1797	855	5572	875	SPL
Ø 52"	Tire size	LI/SS	Rec.	Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
	300/95 R 52	151 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1891	889	5822	925	STD
	300/95 R 52	151 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1891	889	5822	925	SPL
Ø 54"	Tire size	LI/SS	Rec.	Alt.	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
	270/95 R 54	146 A8/B	W 9	W 8 ; W 10	275	1885	894	5815	925	STD
	270/95 R 54	146 A8/B	W 9	W 8 ; W 10	275	1885	894	5815	925	SPL

STD: Standard - SPL: Special



Load Index

The load index is a code that defines a tire's maximum weight capacity at the speed given by its speed symbol provided that the usage conditions recommended by the Manufacturer are fully complied with.

Corresponding values of load index (LI) and load capacity per wheel (kg)

LI	kg	LI	kg	LI	kg	LI	kg
50	190	85	515	120	1400	155	3875
51	195	86	530	121	1450	156	4000
52	200	87	545	122	1500	157	4125
53	206	88	560	123	1550	158	4250
54	212	89	580	124	1600	159	4375
55	218	90	600	125	1650	160	4500
56	224	91	615	126	1700	161	4625
57	230	92	630	127	1750	162	4750
58	236	93	650	128	1800	163	4875
59	243	94	670	129	1850	164	5000
60	250	95	690	130	1900	165	5150
61	257	96	710	131	1950	166	5300
62	265	97	730	132	2000	167	5450
63	272	98	750	133	2060	168	5600
64	280	99	775	134	2120	169	5800
65	290	100	800	135	2180	170	6000
66	300	101	825	136	2240	171	6150
67	307	102	850	137	2300	172	6300
68	315	103	875	138	2360	173	6500
69	325	104	900	139	2430	174	6700
70	335	105	925	140	2500	175	6900
71	345	106	950	141	2575	176	7100
72	355	107	975	142	2650	177	7300
73	365	108	1000	143	2725	178	7500
74	375	109	1030	144	2800	179	7750
75	387	110	1060	145	2900	180	8000
76	400	111	1090	146	3000	181	8250
77	412	112	1120	147	3075	182	8500
78	425	113	1150	148	3150	183	8750
79	437	114	1180	149	3250	184	9000
80	450	115	1215	150	3350	185	9250
81	462	116	1250	151	3450	186	9500
82	475	117	1285	152	3550	187	9750
83	487	118	1320	153	3650	188	10000
84	500	119	1360	154	3750	189	10300

Speed Symbol

The speed code is a value that indicates the maximum admitted speed at which the tire can carry the weight corresponding to its load index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Speed symbol	A1	A2	A3	A4	A6	A8	B	C	D	E	F	J
km/h	5	10	15	20	30	40	50	60	65	70	80	100
mph	3	6	9	12	19	25	31	37	40	43	50	62

Notes



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
 Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica,133
 20831 Seregno (MB), Italy
 Tel: (+39) 0362 33 03 28
 (+39) 0362 32 51 07
 Fax: (+39) 0362 23 24 72

BKT USA Inc.

202 Montrose West, Suite 240
 Copley, (Akron) Ohio 44321, USA
 Tel: (+1) 330 836 1090
 Fax: (+1) 330 836 1091
 Toll Free: (+1) 888 660 0662

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
 Toronto, Ontario M5J 1R7, Canada
 Tel: AG/IND (+1) 905 641 5636
 OTR (+1) 780 888 5667
 Fax: (+1) 416 229 1711



bkt-tires.com

Proud Sponsor of

